

IFC-15T-34N-SRV

Flow Cell

for SRV with 1.5" Tri-Clamp process connection

Description:

Rheonics IFC-15T-34N-SRV accessory is a flow cell used especially on DN5 to DN25 (1") pipes for inline installation of the SRV probe with a 1.5" Tri-Clamp process connection. It can also be used in a bypass, connected via hoses or pipes, for lines bigger than DN25. This flow cell is integrated into the process with 3/4" - 14 NPT inlet and outlet ports and ensures an optimal flow condition for the SRV sensor. The sensor can be easily mounted and removed using the Tri-Clamp connection, allowing an easy inspection and cleaning of the probe.

Specifications:

Sensor Connection	1.5" Tri-Clamp ASME-BPE
Process Connection	3/4" - 14 NPT
Fluid Volume	60 mL
Article Number	27327A
Material	316L



Find out more at:
[IFC-15T-34N-SRV](#)

Related Products:

Sensor	SRV-X3-15T
Closure Clamp	OD 50.5 mm
Gasket	ID 26 mm, OD 50.5 mm

Reference Image:



Please Check for Compatibility!

Before use, please confirm that this accessory and the related products are the right fit for your equipment and application. This includes making sure its materials are compatible with any liquids, gases, or other substances it will contact. Rheonics assumes no liability for damage or malfunction resulting from incompatibility.